## **Options**



	Description	Applicable Models
NEMA 4 Enclosure dust-tight and water-tight	Includes all drains and fittings surrounding the plumbing. Powder-coated white. Includes water-tight window to view the control boards in the electronic models.	All series and models
NEMA 4X Enclosure dust-tight and water-tight stainless steel	Including all drains and fittings surrounding the plumbing. Includes water-tight window to view the control boards in the electronic models.	All series and models
Thermostats	CF Series single-temperature thermostats to control the temperature when the unit heats plus provide over-temperature protection. Select an activation temperature of 90, 110, 125, 145, 155, or 185 °F.	CF all Temperature setting must be selected when ordering
External Kill Switch	Mounted to the outside door of a NEMA 4 or NEMA 4x enclosure and allows the customer to kill power inside the unit by depressing the red button.	Requires NEMA 4 or NEMA 4X en- closure
Mixing Valve	Available for varying output temperatures in 3/4-11/4" sizes	All series and models
Class 1 Division 2	NEMA 4 or NEMA 4X enclosure required	All series and models
<b>Element Indication Lights</b>		All series and models

## **NEMA 3** (standard)

- Made in Florida specifically for Tankless, Inc.
- > Front cover and right side are one piece, hinged, and swing open to allow servicing and element replacement
- > Alpine white color
- Not water resistant





## NEMA 4 & NEMA 4X (optional, watertight) NEMA 3 & NEMA 4 are white

- > NEMA 4X is stainless steel
- > NEMA 4 and NEMA 4X come with watertight fittings, lights, switches, etc., except for drain at bottom
- > Custom window for CE models