

### CK, CKT, & CK Trend Technical Data

#### Technical Data



Certified to ANSI/UL Std. 2021  
Conforms to CAN/CSA Std. 22.2 No. 46



Model	CK 15 E	CKT 15 E	CK 20 E		CKT 20 E		CK 150-1 Trend	CK 200-2 Trend		
Item number	074058	230345	074057		230346		236304	236305		
Voltage	120 V	120 V	240 V or 208 V		240 V or 208 V		120 V	240 V or 208 V		
Wattage	1500 W	1500 W	2000 W	1500 W	2000 W	1500 W	1500 W	2000 W	1800 W	
Amperage	12.5 A	12.5 A	8.3 A	7.2 A	8.3 A	7.2 A	12.5 A	8.3 A	8.7 A	
Rated output Btu/hr	5118	5118	6824	5118	6824	5118	5118	6824	6142	
Air volume	106 CFM	106 CFM	106 CFM		106 CFM		70.6 CFM	70.6 CFM		
Recommended circuit breaker size <sup>1</sup>	15 A	15 A	15 A		15 A		15 A	15 A		
Minimum wire size (copper)	14 AWG	14 AWG	14 AWG		14 AWG		14 AWG	14 AWG		
Timer	no	yes	no		yes		N/A	N/A		
Room size estimate	150 sq.ft.	150 sq.ft.	200 sq.ft.		200 sq.ft.		150 sq.ft.	200 sq.ft.		
Heating element	nichrome wire						ceramic positive temperature coefficient (PTC)			
Thermostat & high limit	bimetal type						bimetal type			
Motor	18 W shaded pole						20 W shaded pole			
Blower	galvanized steel, squirrel cage type						glass-reinforced polycarbonate, radial type			
Dimensions	H 18 <sup>1</sup> / <sub>8</sub> " (460 mm) x W 13 <sup>3</sup> / <sub>16</sub> " (335 mm) x D 4 <sup>3</sup> / <sub>16</sub> " (123 mm)						H 15 <sup>3</sup> / <sub>4</sub> " (400 mm) x W 10 <sup>7</sup> / <sub>8</sub> " (275 mm) x D 5 <sup>1</sup> / <sub>8</sub> " (131 mm)			
Weight	8.0 lb (4.4 kg)						5.5 lb (2.5 kg)			
Temperature range	41-86 °F (5-30 °C)						45-95 °F (7-35 °C)			
Frost protection setting	45 °F (7 °C)						45 °F (7 °C)			
Operating noise	49.7 dB(a)						49.0 dB(a)			

<sup>1</sup> This is our recommendation as the manufacturer. Check local codes for compliance if necessary.