

Galaxy™ & Ultronic™ Technical Specifications

Technical Data



Galaxy™: Certified to ANSI/UL Std. 499 Conforms to CAN/CSA Std. 22.2 No. 36
 Ultronic™: Certified to ANSI/UL Std. 507 Conforms to CAN/CSA C22.2 No. 113

ISO 9001
 CERTIFIED

Hand Dryer Model	Galaxy™ 1	Galaxy™ M 1	Galaxy™ 2	Galaxy™ M 2	Ultronic™ 1 S	Ultronic™ 1 W	Ultronic™ 2 S	Ultronic™ 2 W
Item number	073009	073724	073010	073725	231584	231585	231586	231587
ELECTRICAL DATA								
Phase - 60/50 Hz	single	single	single	single	single	single	single	single
Voltage	120 v	120 v	240 v or 208 v	240 v or 208 v	120 v	120 v	240 v or 208 v	240 v or 208 v
Wattage	1850 w	1850 w	2000 w 1500 w	2000 w 1500 w	985 w	985 w	1000 w 775 w	1000 w 775 w
Amperage	15.42 A	15.42 A	8.34 A 7.21 A	8.34 A 7.21 A	8.5 A	8.5 A	4.3 A 3.85 A	4.3 A 3.85 A
Required circuit breaker size¹	20 A	20 A	15 A	15 A	15 A	15 A	15 A	15 A
Required wire size²	12 AWG	12 AWG	12 AWG	12 AWG	14 AWG	14 AWG	14 AWG	14 AWG
DIMENSIONS								
Height	9 13/16" / 25.0 cm	10 1/2" / 26.6 cm	9 13/16" / 25.0 cm	10 1/2" / 26.6 cm	11 3/8" / 28.9 cm	11 3/8" / 28.9 cm	11 3/8" / 28.9 cm	11 3/8" / 28.9 cm
Width	6 7/8" / 17.5 cm	6 7/8" / 17.5 cm	6 7/8" / 17.5 cm	6 7/8" / 17.5 cm	10 1/8" / 25.7 cm	10 1/8" / 25.7 cm	10 1/8" / 25.7 cm	10 1/8" / 25.7 cm
Depth	9 1/16" / 23.0 cm	9 1/16" / 23.0 cm	9 1/16" / 23.0 cm	9 1/16" / 23.0 cm	9 3/16" / 23.4 cm	9 3/16" / 23.4 cm	9 3/16" / 23.4 cm	9 3/16" / 23.4 cm
WEIGHT								
Weight	5.5 lb / 2.5 kg	8.8 lb / 4.0 kg	5.5 lb / 2.5 kg	8.8 lb / 4.0 kg	9.7 lb / 4.4 kg	9.7 lb / 4.4 kg	9.7 lb / 4.4 kg	9.7 lb / 4.4 kg
CONSTRUCTION								
Color	Alpine White	Alpine White Optional: Charcoal Gray Silver Metallic	Alpine White	Alpine White Optional: Charcoal Gray Silver Metallic	Stainless Steel	Alpine White	Stainless Steel	Alpine White
Housing	ABS polycarbonate	Cast aluminum	ABS polycarbonate	Cast aluminum	Cast aluminum	Cast aluminum	Cast aluminum	Cast aluminum
Degree of protection (IP)	IP 23	IP 23	IP 23	IP 23	IP 23	IP 23	IP 23	IP 23
OTHER								
Sound level	53 dB(a)	53 dB(a)	53 dB(a)	53 dB(a)	82 dB(a)	82 dB(a)	82 dB(a)	82 dB(a)
Air speed	NA	NA	NA	NA	210 mph / 94 m/s	210 mph / 94 m/s	210 mph / 94 m/s	210 mph / 94 m/s
Air volume	90.0 CFM	90.0 CFM	95.0 CFM	95.0 CFM	170.7 CFM	170.7 CFM	170.7 CFM	170.7 CFM
Drying time	30 seconds	30 seconds	30 seconds	30 seconds	15 seconds	15 seconds	15 seconds	15 seconds

¹ This is our recommendation as the manufacturer. Check local codes for compliance if necessary. ² Copper must be used