

## Ultronic™ Plus and Premium & Galaxy™ Hand Dryers

### Technical specifications

Hand Dryer Model	Galaxy™ 1	Galaxy™ M 1	Galaxy™ 2	Galaxy™ M 2	Ultronic™-1 Plus	Ultronic™-1 Premium	Ultronic™-2 Plus	Ultronic™-2 Premium
<b>Item number</b>	073009	073724	073010	073725	205634	205636	205635	205637
<b>ELECTRICAL DATA</b>								
<b>Phase - 60/50 Hz</b>	single	single	single	single	single	single	single	single
<b>Voltage</b>	120 V	120 V	240 V or 208 V	240 V or 208 V	120 V	120 V	240 V or 208 V	240 V or 208 V
<b>Wattage</b>	1850 W	1850 W	2000 W 1500 W	2000 W 1500 W	820 W	820 W	750 W 640 W	750 W 640 W
<b>Amperage</b>	15.42 A	15.42 A	8.34 A 7.21 A	8.34 A 7.21 A	6.8 A	6.8 A	3.5 A 3.5 A	3.5 A 3.5 A
<b>Required circuit breaker size<sup>1</sup></b>	20 A	20 A	15 A	15 A	15 A	15 A	15 A	15 A
<b>Required wire size<sup>2</sup></b>	12 AWG	12 AWG	12 AWG	12 AWG	16 AWG	16 AWG	18 AWG	18 AWG
<b>DIMENSIONS</b>								
<b>Height</b>	9 7/8" (250 mm)	10 1/2" (266 mm)	9 7/8" (250 mm)	10 1/2" (266 mm)	12 3/16" (309 mm)	12 3/16" (309 mm)	12 3/16" (309 mm)	12 3/16" (309 mm)
<b>Width</b>	9 1/16" (230 mm)	9 1/8" (232 mm)	9 1/16" (230 mm)	9 1/8" (232 mm)	10 11/16" (272 mm)	10 11/16" (272 mm)	10 11/16" (272 mm)	10 11/16" (272 mm)
<b>Depth</b>	9 1/16" (230 mm)	9 1/16" (230 mm)	9 1/16" (230 mm)	9 1/16" (230 mm)	5 3/16" (132 mm)	5 3/16" (132 mm)	5 3/16" (132 mm)	5 3/16" (132 mm)
<b>Weight</b>	5.5 lb (2.5 kg)	8.8 lb (4.0 kg)	5.5 lb (2.5 kg)	8.8 lb (4.0 kg)	6.2 lb (2.8 kg)	8.8 lb (4.0 kg)	6.2 lb (2.8 kg)	8.8 lb (4.0 kg)
<b>CONSTRUCTION</b>								
<b>Color</b>	Alpine White	Alpine White Optional: Charcoal Gray Silver Metallic	Alpine White	Alpine White Optional: Silver Metallic	Alpine White	Stainless Steel	Alpine White	Stainless Steel
<b>Housing</b>	ABS polycarbonate	Cast aluminum	ABS polycarbonate	Cast aluminum	Polycarbonate	Stainless Steel	Polycarbonate	Stainless Steel
<b>Degree of protection (IP)</b>	IP 23	IP 23	IP 23	IP 23	IP X3	IP X3	IP X3	IP X3
<b>OTHER</b>								
<b>Sound level</b>	53 dB(a)	53 dB(a)	53 dB(a)	53 dB(a)	76 dB(a)	76 dB(a)	76 dB(a)	76 dB(a)
<b>Air speed</b>	NA	NA	NA	NA	215 mph (96 m/s)	215 mph (96 m/s)	215 mph (96 m/s)	215 mph (96 m/s)
<b>Air volume</b>	90.0 CFM	90.0 CFM	95.0 CFM	95.0 CFM	49.5 CFM	49.5 CFM	49.5 CFM	49.5 CFM
<b>Drying time</b>	30 seconds	30 seconds	30 seconds	30 seconds	10-12 seconds	10-12 seconds	10-12 seconds	10-12 seconds

<sup>1</sup> This is our recommendation as the manufacturer. Check local codes for compliance if necessary. <sup>2</sup> Copper must be used



Galaxy™: Conforms to UL Std. 499 Certified to CAN/CSA Std. 22.2 No. 36  
 Ultronic™: Conforms to UL Std. 50 Certified to CAN/CSA C22.2 No. 113

