

UltraHot Plus® & UltraHot Premium®

Technical specifications

Model	UltraHot Plus®	UltraHot Premium®
Item number	203876	203877
Phase - 50/60 Hz	Single	
Voltage	120 V	
Wattage	750 W	1440 W
Amperage	6.25 A	12 A
Electrical connection	Factory-installed 6 ft. (1.8 m) power cord with plug, hard-wiring optional	
Recommended circuit breaker size¹	10 A	15 A
Warranty	3 years	4 years
Rated capacity	0.7 gal (2.6 l)	
Max. flow rate, hot water	0.66 gpm (2.5 l/min)	
Max. permissible pressure, outlet side	0 psi (0 bar)	
Temperature range	149–203°F (65–95°C)	
User interface	Illuminated LCD display	
Dimensions	H 17 ³ / ₄ " (450 mm) x W 7 ⁷ / ₈ " (200 mm) x D 5 ³ / ₄ " (146 mm)	
Weight	8.0 lb (3.6 kg)	
Frost protection setting	45°F (7°C)	

¹ This is our recommendation as the manufacturer. Check local codes for compliance if necessary.



Conforms to UL Std. 499
Certified to CAN/CSA Std. 22.2 No. 64



Tested and certified by WQA
to NSF/ANSI/CAN 372 for
lead free compliance.

ISO 9001
CERTIFIED