

DHX Select

Technical specifications

Model	DHX 10 Select		DHX 15 Select	
Item no.	208580		204812	
Phase - 50/60 Hz	1			
Voltage	240 V	208 V	240 V	208 V
Wattage	9.6 kW	7.2 kW	14.4 kW	10.8 kW
Amperage	40 A	34.6 A	60 A	52 A
Min. recommended circuit breaker size¹	40 A	35 A	60 A	60 A
Min. recommended wire size²	8/2 AWG		6/2 AWG	
Uniform Energy Factor (UEF)	0.96		0.97	
Recovery efficiency	98%		99%	
Minimum water flow to activate unit	0.264 gpm (1.0 l/min)			
Weight	5.5 lb (2.5 kg)			
Dimensions	Height 14 1/8" (360 mm) x Width 8" (202 mm) x Depth 4 5/16" (109 mm)			
Nominal water volume	0.07 gal (0.277 l)			
Max. permissible inlet temperature	149°F (65°C)			
Maximum permissible pressure	145 psi (10 bar)			
Water connections	1/2" NPT			

¹ Overcurrent protection sized at 100% of load. Tankless water heaters are considered a non-continuous load. Use only GFCI Class A circuit breakers.

² Copper conductors with a temperature rating of 75°C or greater must be used. Conductors should be sized to maintain a voltage drop of less than 3% under load.

These are our recommendations. Check local codes for compliance if necessary.



Conforms to UL Std. 499
Certified to CAN/CSA Std. C22.2 No. 64



Tested and certified by WQA
against NSF/ANSI/CAN 372
for lead free compliance.

ISO 9001
CERTIFIED

